



Olympos ST

multi-purpose hose

универсални маркучи



Specifications

Application: Delivery hose for LIQUIDS, AIR, POWDERED FOODS, SALTS, LIGHT CHEMICALS.

Type of work: delivery

Tube: NON-TOXIC TRANSPARENT PVC

Reinforcement: HIGH TENSILE SYNTHETIC TEXTILE.

Cover: ABRASION, OZONE AND WEATHER RESISTANT TRANSPARENT PVC ALLOWING EASY INSPECTION DURING SERVICE. FOR LIGHT DUTY CONVEYING

Working temperature: -5°C/+60°C (+23°F/140°F)



Характеристики

Приложение: маркуч за пренасяне на течности, въздух, хранителни продукти на прах, сол, леки химикали.







Режим на работа: нагнетателен

Вложка: нетоксично, прозрачно PVC

Подсилване: силноразтегливи синтетични слоеве

Покритие: прозрачно PVC позволяващо лесно инспектиране по време на експлоатация, устойчив на износване, озон и метеорологични условия. За слабо натоварени дейности

Работна температура: -5°C/+60°C (+23°F/140°F)

Вътрешен размер		Външен размер	Работно налягане		Налягане на разкъсване		Тегло	Размер на ролка
								
inch	mm	mm	bar	psi	bar	psi	g/m	m
1"	25	33	10	145	30	435	450	50
1 1/4"	32	40	8	116	24	348	580	50
1 1/2"	38	48	7	102	21	305	880	30
	40	50	6	87	18	261	890	50
	45	55	6	87	18	261	990	50
2"	50	61	6	87	18	261	1200	50