



## Likya ST

### alimentary liquids and light alcohol



#### Speci cations

**Application:** for mineral water, fruit juices, wines, liqueurs up to 15% alcohol contents, alimentary liquids ect.

**Type of work:** suction and delivery

**Tube:** Strong, exible and smooth non-toxic, plasticized PVC

**Reinforcement:** shock resistant PVC spiral

**Cover:** crushing, abrasion and weather resistant, corrugated outside

**Working temperature:** -5°C/+60°C (+23°F/+140°F)

### хранителни течности и слаби алкохоли



#### Характеристики

**Приложение:** за минерална вода, плодови сокове, вино, напитки с алкохолно съдържание до 15%, хранителни течности и други

**Режим на работа:** смукателно-нагнетателен

**Вложка:** гъвкав и гладък, нетоксичен, пластифициран PVC материал

**Подсилване:** устойчива на удар PVC спирала

**Покритие:** устойчив на смачкване, абразия атмосферни влияния, гофрирана повърхност

**Работна температура:** -5°C/+60°C (+23°F/+140°F)

ID		psi		VACUUM	W		
inch	mm	bar	psi	m/H <sub>2</sub> O	mm	g/m	m
3/4"	19	26	377	7	90	280	30/50
1"	25	24	348	6	110	350	30/50
	30	22	319	6	125	440	30/50
	32	21	305	6	130	460	30/50
1 1/4"	35	20	290	6	140	520	30/50
	38	19	276	6	155	570	30/50
	40	19	276	6	165	590	30/50
1 1/2"	45	19	276	6	195	670	30/50
	51	16	232	6	215	830	30/50
	55	15	218	6	225	880	30/50
2"	60	15	218	6	260	950	30/50
	63	15	218	6	275	1000	30/50
	70	13	189	6	310	1150	30/50
2 1/2"	76	13	189	6	335	1450	30/50
	80	13	189	6	350	1530	20/30
	90	13	189	6	415	1750	20/30
3"	102	12	174	6	450	2150	20/30
	110	11	160	5	500	2450	20/30
	120	11	160	5	620	2900	20/30
4"	127	11	160	4	660	3200	20/30
	152	10	145	3	750	4200	20/30